


High temperature resistant ties



Collars & cable ties

Reference : LPS_HT



Single Use : Yes

Material : PA6.6 avec additifs

Total length : De 98 à 200 mm

Width : 2,5 - 3,6 - 4,8 mm

Pull apart force : De 8 à 55 Kg

Metal insert : No

Closure type : Progressive tightening

Ex stock : Yes

Standard packaging : 100 pcs bags

MOQ for stock product : 1.000 pcs

HS Code : 39 23 90 90

Food compatible : No

Detectable : No

Possible Marking : Yes

Delivery Deadline : 4 semaines

Available colors :



These ties are high temperature-proof, between 125 and 145°C, on short periods

Dimensions (mm)	Min. locking diameter	Max. locking diameter	Tensile strength	Qty per carton (minimum and to be ordered by)
2.5 x 98	1 mm	21 mm	80 N	40.000 pcs
3.6 x 140	2 mm	35 mm	130 N	25.000 pcs
3.6 x 200	2 mm	50 mm	130 N	20.000 pcs
4.8 x 200	2 mm	50 mm	220 N	13.000 pcs
4.8 x 290	2.5 mm	79 mm	220 N	10.000 pcs
7.8 x 365	8 mm	100 mm	540 N	3.500 pcs

They comply with UL94V2 fire norms. To tighten better, use a PSP8 tool.

They are available in black or frosted, in 4 to 6 weeks.

Free samples on request

