

# Double wire collar with screw

Cable ties



**Material** : Acier zingué ou Inox

**MOQ for stock product** : 1.000 pcs

These collars are used on smooth tips or spiral ducting

Zinc-plated steel, also available in stainless steel

Application : low pressure sealing on water pipes and air duct connections

Diamètre Diameter	Diamètre idéal d'utilisation Trad	Réf produits products reference	Conditionnement Conditionnement
9,5-12 mm	11 mm	AR12133	500
10,5-13 mm	11,5 mm	AR12134	500
11,5-14 mm	12,5 mm	AR12135	500
12,5-15 mm	13 mm	AR12136	500
13-16 mm	14 mm	AR12137	500
13,5-17 mm	15 mm	AR12138	500
15-18 mm	16 mm	AR12139	500
15,5-19 mm	17 mm	AR12140	500
17-20 mm	18 mm	AR12141	500
17,5-21 mm	18,5 mm	AR12142	500
18,5-22 mm	20 mm	AR12143	500
19-23 mm	20,5 mm	AR12144	500
21-24 mm	22 mm	AR12145	500
21,5-25 mm	23,5 mm	AR12146	500
23,5-27 mm	25 mm	AR12147	500
25-29 mm	27 mm	AR12148	200
27-31 mm	29 mm	AR12149	200
29-33 mm	31,5 mm	AR12150	200
30,5-35 mm	33 mm	AR12151	200
33-37 mm	37 mm	AR12152	200
35,5-40 mm	38,5 mm	AR12153	200
38,5-43 mm	41 mm	AR12154	200
41-46 mm	43,5 mm	AR12155	200
43,5-49 mm	46,5 mm	AR12156	200
46,5-53 mm	50,5 mm	AR12157	200
50,5-56 mm	53,5 mm	AR12158	100
53,5-60 mm	56,5 mm	AR12159	100
56,5-64 mm	60 mm	AR12160	100
60-68 mm	64 mm	AR12161	100
64-72 mm	68,5 mm	AR12162	100
68,5-76 mm	72 mm	AR12163	100
72,5-80 mm	76,5 mm	AR12164	100
76,5-84 mm	80 mm	AR12165	100



2 Avenue Paul Langevin - Zone d'Activités de Ravennes les Francs - 59200 - TOURCOING - France

Phone : +33 3 20 28 87 31 - Fax : +33 3 20 28 87 36

www.etigo.fr - Email : info@etigo.fr

